

SECTION 10800
TOILET AND BATH ACCESSORIES

PART 1 GENERAL

1.1 SECTION INCLUDES

- A. Toilet accessories and their associated fasteners and hardware.

1.2 QUALITY ASSURANCE

- A. Furnish inserts and anchoring devices which must be set in concrete or built into masonry. Coordinate delivery with other Work to avoid delay.
- B. Coordinate accessory locations with other Work to avoid interference and to assure proper operation and servicing of accessory units.
- C. Provide all accessories manufactured by the same company, except for soap dispenser, which must accommodate "Sani-Fresh" soap cartridges.

1.3 SUBMITTALS

- A. Submit the following in accordance with requirements of Section 01300:
 - 1. Catalog data.
 - 2. Manufacturer's installation instructions.

PART 2 PRODUCTS

2.1 MATERIALS, GENERAL

- A. Use stainless steel complying with ANSI Type 302/304, with polished No. 4 finish, 22 gage (0.34 inch) minimum, unless otherwise indicated.
- B. Use leaded and unleaded brass, flat products, complying with FS QQ-B-613; rods, shapes, forgings and flat products with finished edges, FS QQ-B-62.
- C. Use commercial quality, cold rolled, sheet steel complying with ASTM A366, 20 gage (0.040 inch) minimum, unless otherwise indicated. Provide surface preparation and metal pretreatment as required for applied finish.
- D. Use galvanized steel sheet complying with ASTM A527, G60.
- E. Use base metal with nickel and chromium electrodeposited in compliance with ASTM B456, Type SC2.
- F. Use galvanized steel mounting devices complying with ASTM A153, hot dip galvanized after fabrication.
- G. Use screws, bolts, and other devices of same materials as accessory unit or of galvanized steel where concealed.
- H. Use 1/4 inch thick, Type I, Class 1, Quality q2, mirror glass conforming to FS DD-G-451, with silvering, copper coating, and protective organic coating complying with FSS DD-M-411.

2.2 MANUFACTURERS

- A. Bradley Corporation
- B. Bobrick Washroom Equipment Co.
- C. AJ Washroom Accessories
- D. American Specialties Inc. (ASII)

2.3 COMBINATION TOWEL DISPENSER/WASTE RECEPTACLE UNIT

Semi-recessed unit with extended waste receptacle. Provide stainless steel unit made for 4 inch all depth, with continuous 1 inch wall flange. Provide towel dispenser in top of unit, designed for standard core 8 inch or 9 inch wide, 800 feet long. Provide waste receptacle in bottom of unit. Bobrick Model B-3966, Bradley Model 227-10. Symbol PTD.

2.4 SANITARY NAPKIN DISPENSER

Provide surface mounted, stainless steel unit that dispenses both napkins and tampons, coin free. Provide dispensing identification of "Napkins" and "Tampons". Bobrick Model B-254, Bradley Model 426. Symbol SND.

2.5 SANITARY NAPKIN RECEPTACLE

Provide surface mounted, stainless steel unit with self-closing door. Bobrick Model B-254, Bradley Model 4722-15. Symbol SNR.

2.6 TOILET SEAT COVER DISPENSER

Provide surface mounted, stainless steel unit with hinged access door for refilling. Bobrick Model B-221, Bradley Model 583. Symbol TSCD.

2.7 GRAB BARS

Provide 1 1/4 inch OD, stainless steel grab bars with mounting flanges with concealed fasteners. Provide 1 1/2 inch clearance from bar to wall. Provide textured gripping surface. Bobrick Model B-550 Series, Bradley Model 893 Series. Symbol GB.

2.8 SOAP DISPENSER

Provide stainless steel, recessed liquid soap dispenser unit. ASI Model 5002, AJ Model U102. Symbol SD.

2.9 TOILET PAPER DISPENSER

Provide stainless steel, surface mounted dispenser for two rolls, with shelf. Bobrick Model B-2840, Bradley Model 5263. Symbol TPD.

2.10 MIRROR

Provide stainless steel framed mirror with 1/4 inch plate glass mirror. Bobrick Model B-290 Series, Bradley Model 700 Series. Symbol M.

2.11 SHELF

Provide stainless steel, wall mounted shelf, 6 inches wide by 24 inches long. Bobrick Model B-296, Bradley Model 756. Symbol S.

2.12 MOP AND BROOM HOLDER

Provide stainless steel, wall mounted combination mop and broom holder. Bobrick Model B-223x24, Bradley Model 9953. Symbol MBH.

2.13 COAT HOOK

Provide stainless steel coat hooks on inside face of toilet compartment doors. Bobrick Model B-682, Bradley Model 9134. Symbol CH.

2.14 LOCKS

Provide accessories without keyed locks. Modify accessories with locks as standard features to perform as latches only.

2.15 FABRICATION

- A. Only an unobtrusive stamped logo of the manufacturer is permitted on exposed faces of the units. In an unexposed location, place the manufacturer's name and product model number.
- B. Fabricate units with welded and ground joints and edges rolled. Hang doors with continuous stainless steel piano hinges. Provide for concealed anchorage wherever possible.
- C. Mirror fabrication
 - 1. Fabricate frames to accommodate wood, felt, plastic, or other glass edge protection material.
 - 2. Provide galvanized steel backing sheet, no less than 22 gage and full mirror size, with non-absorptive filler material. Corrugated cardboard is not an acceptable filler material.
 - 3. Provide hanger system for tamperproof installation, using galvanized steel wall brackets with concealed locking devices requiring a special tool to remove.

Provide a schedule if job requires one.

2.16 SCHEDULE

- A. Men's Toilet
- B. Women's Toilet
- C. Janitor's Closet

PART 3 EXECUTION

3.1 INSTALLATION

- A. Install accessories in accordance with approved manufacturer's installation instructions.
- B. Securely attach each accessory, level and plumb, at locations shown on the Drawings and at heights, spacing, and load resistance required by ADAAG (Americans with Disabilities Act Accessibility Guidelines).

- C. Use fasteners that are appropriate for surfaces where accessories are to be mounted.
- D. Use concealed fasteners wherever possible.
- E. Secure mirrors in a tamperproof manner.

3.2 CLEANING

- A. Clean stainless steel and mirror surfaces in compliance with manufacturer's instructions.

END OF SECTION